Docket No.:

Amendment dated:

IB-1942

March 4, 2010

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

## Listing of Claims:

1. (currently amended) A solid state electrochemical device, comprising:

an electrically conductive housing member;

at least one unit <u>in electrical contact with said conductive housing member</u>, said unit comprising a first electrochemical cell and a second electrochemical cell, wherein:

each <u>electrochemical</u> cell <u>comprises</u> <u>comprising a laminate of</u> a first <u>fuel</u> electrode and a second <u>air</u> electrode, separated by <u>a planar</u>, solid state electrolyte, <u>said air electrode</u> <u>having a current collector attached thereto</u>, the current collector of at least one of said air <u>electrodes connected to said electrically conductive housing member</u>, the electrolyte <u>having a planar configuration</u>;

the first and second electrochemical cells having a first end and a second end, and sealed to one another by a seal at their first and second ends, the seal at the first end electrically conductive, the seal at the second end electrically insulating, and wherein

each <u>electrochemical</u> cell is positioned adjacent to one another such that electrodes of one type are facing inward toward one another and the electrodes of the other type are each facing outward, and wherein the inwardly spaced electrodes are positioned so as to define a space there between sufficient for passage of a gas during operation of the device.

 (currently amended) The solid state electrochemical device as claimed in claim 1, wherein: March 4, 2010

the first electrochemical cell and the second electrochemical cell each comprise a laminate comprising a first electrode which is a fuel electrode, an electrolyte and a second electrode which is an air electrode having a current collector attached thereto, wherein:

the fuel electrodes are facing inward and opposite each other.

- 3. (cancelled)
- 4. (currently amended) The solid state electrochemical device as claimed in claim [[3]] 1, wherein:

the seal at the first end is electrically conductive and is connected to a housing that is electrically conductive, and the seal at the second end is electrically insulating and is connected to a housing that is electrically conductive, and the current collector of at least one air electrode is attached to the housing.

- 5. (currently amended) The electrochemical device as claimed in claim [[4]] 1, wherein: the current collector is embedded in the air electrode.
- 6. (currently amended) The electrochemical device as claimed in claim [[4]] 1, wherein: the current collector is on top of the air electrode.
- 7. (currently amended) The electrochemical device as claimed in claim [[4]] 1, wherein: the current collector of the air electrode of the first cell is connected to the air electrode of the second cell, and the air electrode of the second cell is electrically connected to the housing member.
- 8. (currently amended) An electrochemical device as claimed in claim [[4]] 1, further comprising:

Docket No.: Amendment dated: IB-1942 March 4, 2010

a plurality of <u>fuel cell</u> units, each unit connected to at least one other adjacent unit, such that during operation of the device current is able to flow from one unit to the adjacent unit.

- 9. (currently amended) An electrochemical device as claimed in claim [[2]] 1, wherein: both air electrodes form an outwardly facing side of the unit and are exposed to ambient air, and the unit has a first side edge and a second side edge, wherein: the first side edge is sealed by a first side edge manifold and the second side edge is sealed by a second side edge manifold, said manifolds defining an enclosed space between the first side edge manifold, the spaced apart fuel electrodes and the second side edge manifold, such that during operation fuel may be passed from the first side edge manifold through the enclosed space between the fuel electrodes and through the second side edge manifold.
- 10. (original) The electrochemical device as claimed in claim 9, further comprising:

  a fuel manifold comprising a first inlet section and a second exhaust section separated
  from the first inlet section, and wherein the first side edge manifold is connected to the
  fuel manifold first inlet section and the second side edge manifold is connected to the fuel
  manifold second exhaust section.
- 11. (original) The electrochemical device as claimed in claim 10, further comprising:

  an electrically insulating seal between the first and second side edge manifolds and the
  fuel manifold.
- 12. (original) The electrochemical device as claimed in claim 11, further comprising: separators disposed in the space between the fuel electrodes.
- 13. (original) The electrochemical device as claimed in claim 10, further comprising: a plurality of units attached to the fuel manifold, wherein:

Docket No.: Amendment dated: IB-1942 March 4, 2010

the units are exposed to ambient atmosphere except where connected to the fuel manifold and the units are electrically connected in series so that current may flow from one unit to another unit.

- 14. (currently amended) The electrochemical device as claimed in claim [[2]] 1, wherein: the fuel electrode and electrolyte of the first electrochemical cell are sealed at a first end, the fuel electrode and electrolyte of the second electrochemical cell are sealed at a first end, and wherein:
  - the seal for the first cell and the seal for the second cell may be the same seal or different seals.
- 15. (original) The electrochemical device as claimed in claim 14, wherein:

  the first and second electrochemical cells are sealed at a first end with an electrically insulating seal, the first and second electrochemical cells are sealed at a second end with an electrically conductive seal, and further comprising:

  air electrodes disposed outwardly of the electrolyte of the first electrochemical cell and the second electrochemical cell.
- 16. (original) The electrochemical device of claim 15, further comprising:
  a current collector attached to the air electrode of the first electrochemical cell, said
  current collector operatively attached to the air electrode of the second electrochemical
  cell.
- 17. (original). The electrochemical device as claimed in claim 15, further comprising:

  a plurality of units, each of said plurality of units having an adjacent unit, and

  wherein the adjacent units are electrically connected by an interconnect wire that

  connects the current collector of the air electrode of the second electrochemical cell to the

  electrically conductive seal of the first electrochemical cell in an adjacent unit.

Docket No.: Amendment dated: IB-1942

March 4, 2010

18. (original) The electrochemical device as claimed in claim 17, wherein: the current collector is embedded in the air electrode.

- 19. (original) The electrochemical device as claimed in claim 17, wherein: the current collector is on top of the air electrode.
- 20. (previously presented) An electrochemical device as claimed in claim 15, wherein: the air electrodes form outwardly facing opposite sides of the unit and are exposed to ambient air, and the unit has a first side edge and a second side edge, wherein: the first side edge is sealed by a first side edge manifold and the second side edge is sealed by a second side edge manifold, said manifolds defining an enclosed space between the first side edge manifold, the spaced apart fuel electrodes and the second side edge manifold, such that during operation fuel may be passed from the first side edge manifold through the enclosed space between the fuel electrodes and through the second side edge manifold.
- 21. (original) The electrochemical device as claimed in claim 15, further comprising: separators disposed in the space between the fuel electrodes.
- 22. (original) The electrochemical device as claimed in claim 15, wherein: the device is a solid oxide fuel cell.
- 23. (cancelled)